



NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS [INCHES].
2. TOUGHENED GLASS THICKNESS: 5.6±0.3mm[0.22±.012]".
3. TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN.
4. NO MATERIAL EXTENDS MORE THAN 0.8mm[0.03"] BEYOND THE BACK SURFACE OF THE GLASS.
5. CABLE IS ROUTED ALONG THE BEVEL EDGES OF THE GLASS.
6. BERG 65043-031, 2x6 HOUSING WITH BERG 48239-000 RECEPTACLES, DIRECTLY MATES WITH ANY OF THE FOLLOWING:
 -INTELLITOUCH SERIAL CONTROL BOARD
 -012226 CABLE (2x6 TO 8" DB9 BULKHEAD)
7. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.
8. SURFACE QUALITY SPECIFICATIONS: ELO'S ESS00051

CONNECTION CHART

PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE (+)	BLU	BLK
4	Y TRANSMIT (+)	BLU	GRY
5	Y RECEIVE (-)	BLK	BLK
6	Y TRANSMIT (-)	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT (-)	RED	RED
9	X RECEIVE (-)	RED	BLK
10	X TRANSMIT (+)	GRN	RED
11	X RECEIVE (+)	WHT	BLK

TOUCHSCREEN TABULATION

PART NUMBER	SURFACE FINISH
E107261	CLEAR

