



# I-Series 2.0 for Android

All-in-One Touchscreen Signage



**Integrated Touch**



**Commercial Grade**



**2-Year Warranty**

## Product Overview

Elo's newly upgraded I-Series 2.0 for Android™ combines commercial-grade reliability with the powerful Android Qualcomm® Snapdragon™ processor. Delivering 2X the performance of its predecessor, the I-Series 2.0 brings it all with an integrated TouchPro® PCAP 10-touch display, Android 7.1 (Nougat) and optional Power-over-Ethernet (POE) - all in a compact responsive AiO computer. Available in white and black, the AiO offers a variety of mounting options with the flexibility needed to survive the rigors of continuous public use for in-store interaction, point of sale, self-service, wayfinding, corporate and hospitality environments.

Combine the I-Series with Elo's cloud-based management software, EloView® designed to simplify and automate deployment of Elo interactive displays across the globe. EloView, a software-as-a-service (SaaS) platform, includes OS management (including remote and silent updates), kiosk lock-down, automatic provisioning and device management. The platform also offers virtual GPS capabilities enabling a location to be set (latitude/longitude) remotely for each device, so that content may be localized per device or across all locations.

**Available in 10", 15" or 22" widescreen sizes with high-performance computing and sleek edge-to-edge glass PCAP touchscreen**

**Power-over-Ethernet and Virtual GPS enable flexible installations and customized content delivery via applications**

**Optimize deployments with cloud-based configuration, monitoring and scheduling**

**Modern design with flexible mounting in portrait, landscape and table-top orientation**

## I-Series 2.0 for Android Touchscreen Signage

Specifications	10-inch model	15-inch model	22-inch model
Bezel Color	Black & White		
Diagonal Size	10.1" (256.54mm)	15.6" (396.24mm)	21.5" (546.10mm)
Operating System	Android 7.1 with EloView content deployment and management		
Processor	Qualcomm® Snapdragon™ APQ8053 2.0GHz octa-core Processor		
Memory	Standard - 3GB DDR3L; Value - 2GB DDR3L		
Storage	Standard - eMMC 5.1 32GB SSD; Value - 16GB SSD		
I/O Ports	Standard - Micro HDMI output, Micro SD slot, Ethernet 1x LAN (Gigabit), GPIO, 1x USB 3.0, 4x microUSB Value - Ethernet 1x LAN (Gigabit), 1x USB 3.0 support, Micro SD slot, GPIO		
Wireless	802.11 b/g/n/ac + Bluetooth 4.1		
Webcam	Auto exposure; Auto Gain Control; Sharpness/Brightness/Contrast control; Max resolution: 1920 x 1080 30fps (standard models only)		
Speakers	Two 2W stereo internal speakers		
Audio	Built-in microphone (standard models only) Microphone and headphone support is available via an optional the USB adapter (Vantech NBA-120U)		
Active Display Area	8.54" x 5.34" (216.96mm x 135.60mm)	13.55" x 7.62" (344.16mm x 193.59mm)	18.74" x 10.54" (476.06mm x 267.79mm)
Display Technology	1280 x 800 @ 60Hz (native) active matrix TFT LCD with LED backlight	Full HD 1920 x 1080 @ 60Hz (native) active matrix TFT LCD with LED backlight	
Touch Technology	TouchPro PCAP (Projected Capacitive) - up to 10 touches		
Aspect Ratio	16:10	16:9	16:9
Number of Colors	8-bit (16.7M)	6-bit (262K)	6-bit (Hi-FRC; 16.7M)
Brightness	LCD Panel 400 nits; PCAP: 344 nits	Standard - LCD Panel 300 nits; PCAP: 258 nits Value - LCD Panel 220 nits; PCAP: 189 nits	LCD Panel 250 nits; PCAP: 215 nits
Response Time	25 ms	Standard - 30 ms; Value - 12 ms	14 ms
Viewing Angle	Horizontal: ±85°; Vertical: ±85°	Standard - Horizontal: ±85°; Vertical: ±85° Value - Horizontal: ±45°; Vertical: 20° & 40°	Horizontal: ±89°; Vertical: ±89°
Contract Ratio	800:1	Standard - 800:1; Value - 500:1	1000:1
Power	AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz		
Power Consumption	ON: 10.2W / OFF: 0.4W / SLEEP: 5.0W	ON: 13W / OFF: 0.4W / SLEEP: 4.5W	ON: 16W / OFF: 0.5W / SLEEP: 4.0W
Power Cables	Included - North American, European or UK		
Dimensions* (W x D x H)	10.06" x 7.13" x 0.99" (255.41mm x 181.11mm x 25.1mm)	15.23" x 9.77" x 1.11" (386.74mm x 248.17mm x 28.3mm)	20.63" x 12.75" x 1.39" (523.9mm x 323.9mm x 35.2mm)
Shipping Dimensions	12.99" x 9.84" x 5.51" (330mm x 250mm x 140mm)	5.90" x 11.81" x 18.50" (150mm x 300mm x 470mm)	7.08" x 15.75" x 23.62" (180mm x 400mm x 600mm)
Weight	Unpackaged: 1.94 lbs (0.88 kg) Packaged: 4.56 lbs (2.07 kg)	Unpackaged: 3.5 lbs (1.59 kg) Packaged: 7.20 lbs (3.27 kg)	Unpackaged: 9.47 lbs (4.3 kg) Packaged: 16.10 lbs (7.30 kg)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)		
Humidity	Operating: 20%-80%; Storage: 5%-95%		
Mounting Options	75 mm x 75 mm	75mm x 75mm & 100mm x 100mm	100mm x 100mm
Peripheral Mounting	Standard - 4x microUSB side ports available; Value - Peripheral mounting is not available		
Real-Time Clock	Lithium-ion battery		
Sealing	Touchscreen sealed to LCD		
MTBF	50,000 hours demonstrated		
Warranty	2 years standard. On-site exchange (U.S. only) and extended warranty (U.S. and EMEA) available		
Regulatory Approvals	UL/cUL, FCC, IC, CE, CB, CCC, SRRC, China RoHS, VCCI, MIC, RCM (Australia)		
What's in the Box	I-Series 2.0 device, North American Power Cable, European or UK Power Cable, 1x Power Brick, Quick Install Guide, Screws for cable cover door (located in the power/Ethernet bay)		

## Ordering Information

Family	Part Number	Description	Color	Memory	Storage	Availability
Standard versions	E610902	ESY10i1-2UWA-0-NA-GY-G	Black	3GB	32GB	Worldwide
	E611296	ESY15i1-2UWB-0-AN-GY-G	Black			Worldwide
	E611675	ESY22i1-2UWB-0-AN-GY-G	Black			Worldwide
	E614194	ESY10i1-2UWB-0-AN-WH-G	White			Worldwide (MTO)
	E614592	ESY15i1-2UWB-0-AN-WH-G	White			Worldwide (MTO)
E614981	ESY22i1-2UWB-0-AN-WH-G	White	Worldwide (MTO)			
Value versions	E611101	ESY10i1-2UWC-0-AN-GY-G	Black	2GB	16GB	Worldwide
	E611480	ESY15i1-2UWC-0-AN-GY-G	Black			Worldwide
	E614391	ESY10i1-2UWC-0-AN-WH-G	White			Worldwide (MTO)
	E614786	ESY15i1-2UWC-0-AN-WH-G	White			Worldwide (MTO)

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### North America

Tel +1 408 597 8000  
Fax +1 408 597 8050  
elosales.na@elotouch.com

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
elosales@elotouch.com

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
www.elotouch.com.cn

### Latin America

Tel +52 55 2281 6958  
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and EloView are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.  
© 2018 Elo Touch Solutions, Inc. All rights reserved. 18031AES00010

